



**Amerex Corporation**

Quality is Behind the Diamond®



**Wheeled Extinguishers**

# STORED PRESSURE

## 50, 125/150 lb. Stored Pressure ABC, REGULAR, PURPLE K Dry Chemical

These commercial stored pressure extinguishers are available in a choice of two sizes and three chemical options. The carriage design on both sizes provides cage type protection for the agent cylinder as well as a well balanced platform for transportation and operation. The narrow width and easy rolling semi-pneumatic rubber tire wheels allow one person movement through narrow aisles, doorways and in confined areas. Chemical and pressure is sealed in the agent cylinder, ready for instant actuation and is always protected from contamination. Stored pressure wheeled extinguishers are less expensive to purchase as well as easier and less costly to maintain and service.

**Exclusive features:** Brass fittings, live swivels



SPECIFICATIONS	50 LB. DRY CHEMICAL			125/150 LB. DRY CHEMICAL		
MODEL NUMBER	495	496	497	488	489	490
AGENT TYPE	ABC	REGULAR	PURPLE K	ABC	REGULAR	PURPLE K
UL & ULC RATING	20A:160B:C	160B:C	160B:C	30A:240B:C	240B:C	320B:C
CAPACITY (LBS.)	50 / 22.68			125 / 56.7	150 / 68.0	125 / 56.7
SHIPPING WT. (LBS.)	174 / 78.88			344 / 155.95	369 / 167.28	344 / 155.95
HEIGHT (IN./CM)	46 / 116.84			53.5 / 136.0		
WIDTH (IN./CM)	21.5 / 54.61			28 / 71.12		
DEPTH (IN./CM)	24 / 60.96			40 / 101.6		
DISCHARGE TIME (SEC.)	35			48		
DISCHARGE RANGE (FT./M)	25-35 / 7.62 - 10.66			30-40 / 9.1-12.2		
OPERATING TEMP. (F/C)	-40° to +120° / -40° to +49°			-65° to 120° / -54° to +49°		
HOSE LENGTH (FT./M)	25 / 7.62			50 / 15.2		
HOSE DIAMETER (IN./CM)	.50 / 1.27			.75 / 1.90		
WHEELS [SEMI-PNEU] (IN./CM)	12.5 X 3.5 / 31.75 X 8.89			16 X 4 / 40.64 X 10.16		
USCG APPROVED	YES					



### Available Options:

- Stationary Design

### TEST STANDARDS:

CAN/ULC S504 & ANSI/UL 229  
CAN/ULC S508 & ANSI/UL 711

### Available Options:

- Stationary Design
- Tow Loop

## HIGH PERFORMANCE 125/250 lb. Stored Pressure ABC, REGULAR, PURPLE K Dry Chemical

HIGH PERFORMANCE Stored Pressure units are the finest performing dry chemical wheeled fire extinguishers available anywhere! They have a tremendous flow rate, vertical and horizontal range, fire killing ability and operator protection. Wheels are wide footprint 36" X 6".

**Exclusive features:** Hot dip galvanized carriage and wheels, special corrosion resistant paint finish, lift eyes on carriage (250 lb. models only)

Exclusive 12 year warranty!



SPECIFICATIONS	DRY CHEMICAL			
MODEL NUMBER	573	574	575	690
AGENT TYPE	ABC	REGULAR	PURPLE K	PURPLE K
UL & ULC RATING	40A:160B:C	160B:C	160B:C	120B:C
CAPACITY (LBS.)	250 / 113.4			125 / 56.7
SHIPPING WT. (LBS.)	775 / 351.3			400 / 181.4
HEIGHT (IN./CM)	60 / 152.4			53.5
WIDTH (IN./CM)	37 / 93.98			34
DEPTH (IN./CM)	44 / 111.76			38.5
DISCHARGE TIME (SEC.)	50	40	42	30
DISCHARGE RANGE (FT./M)	60 - 80 / 18.19 - 24.26			50 - 55 / 15.24 - 16.76
OPERATING TEMP. (F/C)	-40° to +120° / -40° to +49°			
HOSE LENGTH (FT./M)	50 / 15.24			
HOSE DIAMETER (IN./CM)	1 / 2.54			
WHEELS [STEEL] (IN./CM)	36 X 6 / 91.44 X 15.24			
USCG APPROVED	YES			



### Available Options:

- Optional 36" x 6" wheels with non-sparking rubber treads
- Stationary Design

### TEST STANDARDS:

CAN/ULC S504 & ANSI/UL 229  
CAN/ULC S508 & ANSI/UL 711

### Available Options:

- Optional 36" x 6" wheels with non-sparking rubber treads
- Stationary Design

# NITROGEN CYLINDER OPERATED

## 125/150, 300/350 lb. Direct Pressure

### ABC, REGULAR, PURPLE K Dry Chemical

125 lb. ABC & Purple K and 150 lb. Regular Direct Pressure extinguishers utilize a 23 ft<sup>3</sup> nitrogen cylinder with a "quick opening valve" to pressurize and completely discharge the agent cylinder. The compact size and 16" semi-pneumatic tires allow easy maneuvering and operation by one person, through narrow doorways and aisles. A 4" stainless steel fill opening with rugged brass cap makes servicing easier. For large hazards choose the 300 lb. ABC or Purple K or 350 lb. Regular Direct Pressure extinguishers with a "quick opening" 55 ft<sup>3</sup> nitrogen cylinder. They provide quality and economical fire protection, large volume capacity for extra high hazard areas with single person transport and operation. The 36" X 6" wide steel wheels make movement possible in sandy or soft soil. **Exclusive features:** Stainless steel collars, chrome plated brass cap, brass fittings, live swivels and bi-lingual labels. Meets Transport Canada requirements.



#### Available Options:

- Stationary Design
- Pressure Indicator

SPECIFICATIONS	125/150 LB. DRY CHEMICAL			300/350 LB. DRY CHEMICAL		
MODEL NUMBER	450	451	452	491	492	493
AGENT TYPE	ABC	REGULAR	PURPLE K	ABC	REGULAR	PURPLE K
UL & ULC RATING	30A:240B:C	240B:C	320B:C	40A:320B:C	320B:C	320B:C
CAPACITY (LBS.)	125 / 57	150 / 68	125 / 57	300 / 136.07	350 / 158.75	300 / 136.07
SHIPPING WT. (LBS.)	335 / 152	360 / 163	335 / 152	743 / 337.01	793 / 359.69	743 / 337.01
HEIGHT (IN./CM)	45 / 115			57 / 144.78		
WIDTH (IN./CM)	24 / 61			34 / 86.36		
DEPTH (IN./CM)	36 / 92			39 / 99.06		
DISCHARGE TIME (SEC.)	52	60	53	60	70	67
DISCHARGE RANGE (FT./M)	30 - 40 / 9 - 12					
OPERATING TEMP. (F/C)	-65° to +120° / -54° to +49°					
NITROGEN CYLINDER (CU. FT. / LITER)	23 / 651			55 / 1557.43		
SAFETY BURST DISC RANGE (PSI / kPa)	400 - 500 / 2760 - 3450					
HOSE LENGTH (FT./M)	50 / 15.24					
HOSE DIAMETER (IN./CM)	.75 / 1.90			1 / 2.54		
WHEELS [SEMI-PNEUMATIC / STEEL] (IN./CM)	16 X 4 / 40.64 X 10.16			36 X 6 / 91.44 X 15.24		
USCG APPROVED	YES					
FM APPROVED			YES			YES

#### TEST STANDARDS:

CAN/ULC S504 & ANSI/UL 229  
CAN/ULC S508 & ANSI/UL 711



#### Available Options:

- 36" x 6" wheels with non-sparking rubber treads
- 75 ft. hose
- Stationary Design
- Pressure Indicator

## 125/150 lb. Regulated Pressure

### ABC, REGULAR, PURPLE K Dry Chemical

These 110 ft<sup>3</sup> nitrogen cylinder operated models feature a pressure regulator and two wheel options. The older, traditional design allows for adequate pressure to assure a smooth, complete discharge of the dry chemical with pressure reserve for blowing down the discharge hose. Choose either the 16" semi-pneumatic rubber tire or 36" X 2½" steel wheels according to the area to be protected. Easy to transport and operate by one person.

**Exclusive features:** Stainless steel collars, chrome plated brass cap, brass fittings, live swivels and bi-lingual labels. Meets Transport Canada requirements.



#### Available Options:

- Stationary Design
- Pressure Indicator

SPECIFICATIONS	125/150 LB. DRY CHEMICAL			300/350 LB. DRY CHEMICAL		
MODEL NUMBER	467	468	469	470	471	472
AGENT TYPE	ABC	REGULAR	PURPLE K	ABC	REGULAR	PURPLE K
UL & ULC RATING	30A:240B:C	240B:C	320B:C	30A:320B:C	240B:C	320B:C
CAPACITY (LBS.)	125 / 57	150 / 68	125 / 57	125 / 57	150 / 68	125 / 57
SHIPPING WT. (LBS.)	404 / 183	429 / 195	404 / 183	432 / 196	457 / 207	432 / 196
HEIGHT (IN./CM)	52 / 132					
WIDTH (IN./CM)	26 / 66			28 / 71		
DEPTH (IN./CM)	38 / 97			45 / 114		
DISCHARGE TIME (SEC.)	48	53	52	48	53	52
DISCHARGE RANGE (FT./M)	30 - 40 / 9 - 12					
OPERATING TEMP. (F/C)	-65° to +120° / -54° to +49°					
NITROGEN CYLINDER (CU. FT. / LITER)	110 / 3115					
HOSE LENGTH (FT./M)	50 / 15.24					
HOSE DIAMETER (IN./CM)	.75 / 1.90					
WHEELS (SEMI-PNEUMATIC / STEEL) (IN./CM)	16 X 4 / 40.64 X 10.16			36 X 6 / 91.44 X 15.24		
USCG APPROVED	YES					
FM APPROVED			YES			YES

#### TEST STANDARDS:

CAN/ULC S504 & ANSI/UL 229  
CAN/ULC S508 & ANSI/UL 711



#### Available Options:

- 36" x 6" or 36" x 2½" wheels with non-sparking treads
- Stationary Design
- Pressure Indicator

# SPECIAL APPLICATION EXTINGUISHERS

## 33 Gal. Direct Pressure Premix FFFP Foam

The Model 630 contains a premixed FFFP (film forming fluoroprotein) alcohol resistant foam which is highly effective on Class B fuel fires and a penetrating and wetting agent on fires involving Class A materials. Excellent when used as a vapor suppressant on fuel spills to prevent ignition. Quality hardware throughout including the **unique agent cylinder fabricated entirely of stainless steel - no interior coatings are necessary.** Model 630 meets NFPA requirements for hospital helicopter pad protection.

**Exclusive features:** Brass fittings, stainless steel collar, brass cap, live swivels.



### Available Options:

- Optional 36" x 6" wheels with non-sparking rubber treads
- Stationary Design
- Pressure Indicator

SPECIFICATIONS	33 GAL. FOAM
MODEL NUMBER	630
AGENT TYPE	FFFP (ALCOHOL RESISTANT)
UL & ULC RATING	20A:160B
CAPACITY (GAL. / LITER)	33 / 124.91
SHIPPING WT. (LBS.)	390 / 176.88
HEIGHT (IN./CM)	57 / 144.78
WIDTH (IN./CM)	34 / 86.36
DEPTH (IN./CM)	39 / 99.06
DISCHARGE TIME (SEC.)	60
DISCHARGE RANGE (FT./M)	30 - 40 / 9.1 - 12
OPERATING TEMP. (F/C)	+35° to 120° / +2° to +49°
NITROGEN CYLINDER (CU. FT. / LITER)	23 / 651.29
SAFETY BURST DISC RANGE (PSI / kPa)	400 - 500 / 2760 - 3450
HOSE LENGTH (FT./M)	50 / 15.2
HOSE DIAMETER (IN./CM)	1 / 2.54
WHEELS [STEEL] (IN./CM)	36 X 6 / 91.44 X 15.24
USCG APPROVED	YES

### TEST STANDARDS:

CAN/ULC S554 & ANSI/UL 8  
CAN/ULC S508 & ANSI/UL 711

## 150 lb. Regulated Pressure SODIUM CHLORIDE

## 250 Lb. Regulated Pressure COPPER Powder CLASS D Dry Powder

Two choices for large volume Class D (flammable metal) protection. Model 680 (Sodium Chloride) is effective on magnesium, sodium, potassium and sodium potassium alloy fires. Model 681 (Copper Powder) designed particularly for fighting difficult lithium fires. Well balanced for quick transport on 36" non-sparking rubber tread steel wheels. Both are pressurized with Argon and regulated to a low 125 psi to avoid disrupting the burning materials.



### Extension Wand is Standard

**Exclusive features:** Brass fittings, stainless steel collar, brass cap, live swivels.

### Available Options:

- Pressure Indicator
- Nozzle

SPECIFICATIONS	CLASS D	
MODEL NUMBER	680	681
AGENT TYPE	SUPER D (SODIUM CHLORIDE)	COPPER
CAPACITY (LB.)	150 / 68	250 / 113.33
SHIPPING WT. (LBS.)	444 / 201.28	544 / 246.61
HEIGHT (IN./CM)	52 / 132.08	
WIDTH (IN./CM)	28 / 71.12	
DEPTH (IN./CM)	45 / 114.3	
DISCHARGE TIME (SEC.)	80	120
DISCHARGE RANGE (FT./M)		
WITH NOZZLE	20 - 30 / 6.57 - 9.86	
WITH APPLICATOR	4 - 8 / 1.31 - 2.62	
OPERATING TEMP. (F/C)	-40° to 120° / -40° to +49°	
NITROGEN CYLINDER (CU. FT. / LITER)	110 / 3115	
HOSE LENGTH (FT./M)	25 / 7.70	
HOSE DIAMETER (IN./CM)	.75 / 1.90	
WHEELS [STEEL] (IN./CM)	36 X 2.5 / 91.44 X 15.24	
USCG APPROVED	NO	
FM APPROVED	YES	

### TEST STANDARDS:

CAN/ULC S504 & ANSI/UL 229  
CAN/ULC S508 & ANSI/UL 711

## 50 & 100 lb. CARBON DIOXIDE

Large volume CO<sub>2</sub> protection provided in either 50 or 100 lb. (2 - 50 lb. cylinders) government specification wheeled extinguishers. Rugged construction and easy to operate with a "quick opening" 'T' handle valve and horn mounted shut-off valve. A logical choice in areas where a Class B:C non-contaminating agent is required and where hand portable extinguishers are not available.



### Available Options:

- Stationary Design

SPECIFICATIONS	CARBON DIOXIDE	
MODEL NUMBER	333	334
AGENT TYPE	CARBON DIOXIDE	
UL & ULC RATING	20B:C	
CAPACITY (LB.)	50 / 22.7	100 / 45.4
SHIPPING WT. (LBS.)	257 / 116.6	461 / 209.3
HEIGHT (IN./CM)	47 / 119.5	
WIDTH (IN./CM)	23 / 58.4	
DEPTH (IN./CM)	48 / 122	
DISCHARGE TIME (SEC.)	44+5	74+8
DISCHARGE RANGE (FT./M)	10 - 15 / 3.04 - 4.57	
OPERATING TEMP. (F/C)	-22° to +120° / -30° to +49°	
HOSE LENGTH (FT./M)	40 / 12.1	
HOSE DIAMETER (IN./CM)	.25 / .635	
WHEELS [FULL PNEUMATIC] (IN./CM)	16 X 4 / 40.64 X 10.16	
USCG APPROVED	YES	

### TEST STANDARDS:

CAN/ULC S503 & ANSI/UL 154  
CAN/ULC S508 & ANSI/UL 711

# CLEAN AGENT EXTINGUISHERS

## 65 lb. & 150 lb. - Stored Pressure Halotron I™



16657

The Amerex Halotron I™ extinguishers feature the same qualities found in all Amerex products and adds the convenience of a "clean" extinguishing agent. Halotron I™ extinguishing agent has proven itself as the leader in the hunt for an alternative "clean" agent by being the only alternative "clean" agent to obtain FAA approvals for both ramp use (ARFF Vehicle) and on-board an aircraft. Combining the quality of Amerex products with a proven alternative "clean" agent, the Amerex Halotron I™ wheeled extinguishers offer you the best value in the industry.

⇒ **EPA approved "Clean Agent" for Class A, B, and C hazards**

⇒ **Low GWP (Global Warming Potential)**

⇒ **Low ODP (Ozone Depletion Potential)**

⇒ **Short Atmospheric Lifetime**

⇒ **Maximum visibility during discharge**

⇒ **No thermal or static shock**

⇒ **No electrical conductivity back to the operator**



16684

### Exclusive features:

Brass fittings, live swivels, reflective stripes, tow loops

### Available Options:

36" X 6" wheels with non-sparking rubber treads

### TEST STANDARDS:

CAN/ULC S556 & ANSI/UL 2129

CAN/ULC S508 & ANSI/UL 711



16670

SPECIFICATIONS		HALOTRON I™	
MODEL NUMBER	673	674	675
AGENT TYPE	HALOTRON I™		
UL & ULC RATING	4A:60B:C	10A:80B:C	
CAPACITY (LBS.)	65 / 29.5	150 / 68	
SHIPPING WT. (LBS.)	286 / 129.7	512 / 232.2	610 / 276.7
HEIGHT (IN./CM)	58 / 147.3	64 / 162.6	
WIDTH (IN./CM)	28 / 71.1	30 / 76.2	37 / 94
DEPTH (IN./CM)	39 / 99.1	42 / 106.7	43 / 109.2
DISCHARGE TIME (SEC.)	22	38	
DISCHARGE RANGE (FT./M)	30 - 45 / 9.1 - 13.7		
OPERATING TEMP. (F/C)	-40° to 120° / -40° to +49°		
HOSE LENGTH (FT./M)	50 / 15.2		
HOSE DIAMETER (IN./CM)	.75 / 1.9		
WHEELS [SEMI-PNEUMATIC / STEEL] (IN./CM)	16 X 4 / 40.64 X 10.2		36 X 2.5/ 91.44 X 15.24
USCG APPROVED	NO		



## **Amerex Corporation**

7595 Gadsden Hwy. • P.O. Box 81

Trussville, AL 35173

Ph: (205) 655-3271

Fax: 1-800-654-5980

Int'l Fax: (205) 655-0584

[www.amerex-fire.com](http://www.amerex-fire.com)  
[sales@amerex-fire.com](mailto:sales@amerex-fire.com)



**ISO 9001 - Quality**  
**ISO 14001 - Environmental**  
**OHSAS 18001 - Safety**  
**CERTIFIED FIRM**

**For more information please contact:**



Amerex Corporation makes every attempt possible to provide the most current and updated information. Information contained within this brochure is deemed to be as accurate as possible as of the printing date. Routine changes to products, codes and standards, and warranties subsequent to this printing will supersede printed information. Please contact Amerex Corporation for any revisions, updates, or product changes.